CG X black





Practical usage...



TECHNICAL FEATURES

The choice of emptying black cartridges filled through nozzles into either waste or tank.

Filling black cartridges automatically with a single touch.

A design that does not necessitate vacuum chamber owing to the dripping method filling specialty.

Easy filling with special ink sensitive needles that control ink level.

Automatic signaling system when the cartridge is filled, not filled defected or clogged.

Automatic servicing system. The machine shows the defective system in the machine at the opening by testing all the components.

The machine automaticlly fills: HP 26/29/14 -- HP 45/15 -- HP 56/27/336/338/339/21 -- LEX 16/17 etc.

Filling all black sponge filled cartridges through sensitive needle.

A digital counter recording how many filling operations have been performed or failed to be performed.

Full digital control of refilling.

Full digital control of setting adjusments(the sensitivity of the needles, the timing and speed of refilling, the period of vacuuming and cleaning etc.)

Electronic signaling system (buzzer).

Low energy consumption.

Portable bottles. Ink tanks are not stable on the machine.

Turkish, English, German and French language selection is possible.

Desired ink quantity can be filled with clips in B models.

Every new cartridge model can be filled via additional clips and sensitive needles (In B models).

Easy change of the brand of ink or practically using the inks of different cartridge models since the machine can clean and vacuum inside the tubes and there will be no remaing old ink.

A design that does not necessitate any additional appliance.

Micro processor control.

2x16 LCD screen.

Dimensions: Ex 0601 Black B: 270x290x290 mm.

Weight: \pm 6-6,5 kgs.

Voltage: 220 V